

User Information Sheet

RONCO Item No

PRO-TEC **Brand Name**

Industrial N95 Respirator, Flat Folded Description

Made in Canada

: Non-woven Polypropylene Material

Colour

: • Particulate Filter Efficiency in accordance with Health Canada and NIOSH Characteristics 42 CFR Part 84 (TEB-APR-STP-0059) evaluation: ≥95%

 Breathing resistance/Differential Pressure: a. Inhalation: <35 mmH₂O (343.2 Pa); b. Exhalation: <25 mmH₂O (245.2 Pa)

• Bacterial Filtration Efficiency (ASTM F2101-19): 100% BFE

• Ability to withstand 10 N (0.98 kgf) at connection points of each

Standards : Meets Health Canada guidelines for N95 respirators.



Item number	6204
Inner Layer Material	Spunbond Polypropylene (pp), 30 gsm
Filter Media	2× layers polypropylene (pp) meltblown, 25gsm
Outer Layer	Spunbond polypropylene (pp), 50 gsm
Supportive layer	Non-woven polypropylene (pp), 65 gsm
Adjustable Nose Clip	Double wire laminated – 80-85 mm × 7mm
Nose foam	Latex-free biocompatible foam, 100 mm × 12mm
Elastic Head band	Latex-free elastic – width 6.0 mm
Upperstrap	265-280 mm
Lowerstrap	260-275 mm

Packaging

Product Features

: 6204 - 20 masks x 6 bags = 120 masks per case

. The lightweight, flat-fold designed respirator helps provide quality, reliable, and convenient worker

respiratory protection especially in the industrial environment

• Individual automated packaging helps protect the respirator from contamination before use

Sanding

Bagging

Cleaning

Griding

- · Compatible with a variety of eyewear
- Sculpting of top panel helps conform to eye and nose contours of the face ensuring more room for eyewear
- Embossed top panel facilitates in reduction of eyewear fogging
- · Adjustable nose clip with soft and comfortable fog-reducing foam
- This respirator contains no components made from natural rubber latex
- · High-quality nose-clip ensures proper fit to all facial contours.
- Headstraps are 100% latex-free to minimize risks of allergic reactions.
- One Size Fits All.

Recommended Applications: • Airbone Biological Particles

- - Assembly & Mechanical
 - Foundry Operation
 - Petrochemical Manufacturing
 - Dry Chemical Handling
 - Paint Preparation

 - Composite Finishing

Recommended Industries:

- : Commercial Buildings
 - **Design & Constructions**
 - General Manufacturing
 - Construction
- Heavy Infrastructure
- Mining, Oil & Gas
- Food Safety
- Transportation
- Food Processing

Storage & Handling

: Store in original packaging in a cool,dry and well-ventilated area, away from dust, direct sunlight, moisture and excessive heat (-20 to +30°C) (-4 to +86°F). Avoid direct contact with the used mask. Put it in a plastic bag and discard used masks into a proper lidded trash bin.

Instructions & Restrictions For Use:

- Before use, the wearer must read and understand the User Instructions provided as a part of the product packaging.
- This product is for single use and should be discarded after each use or a maximum of 8 hours of continuous use.
- Do not use in atmospheres containing less than 19.5% oxygen.
- Do not use in atmospheres immediately dangerous to life or health (IDLH).
- Do not exceed maximum use concentrations established by regulatory standards.
- Failure to properly use and maintain this product could result in injury or death.
- All approved respirators shall be selected, fitted, used and maintained in accordance with OSHA, CSA and other applicable regulations. This respirator does not have any replacement parts.
- This respirator helps protect against certain particulate contaminants but does not eliminate exposure to or the risk of contracting any disease or infection.
- . Misuse may result in sickness or death.

