

## **User Information Sheet**

focus on quality

**RONCO** Item No : 6313 **PRO-TEC** Brand Name Industrial N95 Respirator, Vertical Folded Description Made in Canada : Non-woven Polypropylene and polyethylene Material Colour : White : • Particulate Filter Efficiency in accordance with Health Canada and NIOSH Characteristics 42 CFR Part 84 (TEB-APR-STP-0059) evaluation: ≥95% • Breathing resistance/Differential Pressure: a. Inhalation: <35 mmH<sub>2</sub>O (343.2 Pa); b. Exhalation: <25 mmH<sub>2</sub>O (245.2 Pa) • Bacterial Filtration Efficiency (ASTM F2101-19): 100% BFE Ability to withstand 10 N (0.98 kgf) at connection points of each headstrap Standards : Meets Health Canada guidelines for N95 respirators. Item number 6313 Specification Inner Layer Material Spunbond Polypropylene (pp), 30 gsm 2× layers polypropylene (pp) meltblown, 25gsm Filter Media Outer Layer Spunbond polypropylene (pp), 50 gsm Hot-wind non-woven polypropylene (PP) and polyethylene (PE) 45 gsm Supportive layer Adjustable Nose Clip Double wire laminated - 92-97 mm × 5mm Nose foam Latex-free biocompatible foam, 150 mm × 25 mm Elastic Head band Latex-free elastic - width 6.0 mm Upperstrap 250-265 mm Lowerstrap 225-240 mm : 6313 - 30 masks x 6 bags = 180 masks per case Packaging Product Features • The lightweight, vertical folded design of the respirator provides reliable, and convenient worker respiratory protection especially in the industrial environment · Individual automated packaging helps protect the respirator from contamination before use Compatible with a variety of evewear · Conforms to eye and nose contours of the face ensuring more room for eyewear Adjustable noseclip with soft and comfortable fog-reducing foam • This respirator contains no components made from natural rubber latex · High-quality noseclip ensures proper fit to all facial contours • Headstraps are 100% latex-free to minimize risks of allergic reactions • One Size Fits All Recommended Applications : 
Airbone Biological Particles Recommended Industries: : • Commercial Buildings Assembly & Mechanical Sanding Design & Constructions • Foundry Operation Bagging General Manufacturing • Petrochemical Manufacturing Cleaning Construction • Dry Chemical Handling • Griding Heavy Infrastructure Paint Preparation Mining, Oil & Gas Composite Finishing Food Safety Transportation Food Processina Storage & Handling : Store in original packaging in a cool, dry and well-ventilated area, away from dust, direct sunlight, moisture and excessive heat (-20 to +30°C) (-4 to +86°F). Avoid direct contact with the used mask. Put it in a plastic bag and discard used masks into a proper lidded trash bin. Instructions & Restrictions For Use: Before use, the wearer must read and understand the User Instructions provided as a part of the product packaging. • This product is for single use and should be discarded after each use or a maximum of 8 hours of continuous use. Do not use in atmospheres containing less than 19.5% oxygen. · Do not use in atmospheres immediately dangerous to life or health (IDLH). · Do not exceed maximum use concentrations established by regulatory standards.

- Failure to properly use and maintain this product could result in injury or death.
- All approved respirators shall be selected, fitted, used and maintained in accordance with OSHA, CSA and other applicable regulations. This respirator does not have any replacement parts.
- This respirator helps protect against certain particulate contaminants but does not eliminate exposure to or the risk of contracting any disease or infection.
- Misuse may result in sickness or death.